

TOUCHMONITOR

» 15.0" touchmonitor with All-Interface Board, designed for flat positioning. Fully modular: compatible with entire FREE product range.

FREE+

TMC-XMCV-C15-200 15.0" touchmonitor with audio



SPECIFICATION

- » 15.0" touchmonitor with All-Interface Board
 - Dual (USB and RS232) touchmonitor interface
 - Triple (USB and PS/2 and RS232) interface Tipro controller
 - Dual (USB and analogue) interface audio - optional
- » Internal audio option (2x1W loudspeakers with a special microphone amplifier)

TFT LCD properties

- » Native resolution: 1024 x 768 (XGA)
- » Luminance/Brightness: ≥ 400 cd/m²
- » Contrast ratio: $\geq 400 : 1$
- » Backlight lifetime: $\geq 50,000$ hours

Touch panel properties

- » Technology: 5-wire resistive (ELO)
- » Accuracy: ± 2.03 mm
- » Resolution: 4096x4096 touch points
- » Light transmission: 80 \pm 5% (by 550 nm)
- » Lifetime: 35x10⁶ touches in one location

Integrated audio option

- » Loudspeakers: dynamic, stereo 2 x 2W nominal electric power
- » Loudspeaker amplifiers: stereo, 2 x 2W maximal electric output power
- » Loudspeaker amplifiers: logarithmic, with noise gating and compression features
- » Interface: USB (via internal hub) or analogue

ACCESSORY

- TM-VPB** - Power supply
- TM-C2E** - Power cord
- TM-CVV** - VGA cable
- TM-CU1** - USB cable
- TM-CGH** - RS232 touchmonitor cable
- TM-CSA** - PS/2+RS232 controller cable
- TM-CLR** - Analogue audio cable

Native display resolution:

TMC-XMCV-C15-200 1024x 768 (XGA)

Dimensions:

389 x 312 x 109 mm, 4850 g

Packaging dimensions:

665 x 357 x 150 mm, 6800 g

